



TREE-LOPPER



Whole Tree Felling
Boundary Restoration
Tree Pruning
Woodland Maintenance
Thinning & Coppicing
Waste Timber Processing

- The new Tree Lopper (TL) range of rotating shears designed and built in the UK.
- To suit excavators from 1.5t - 14t; also available for loaders, skid steers and telehandlers.
- Manufactured using high grade structural and wear-resistant steels, for exceptional durability.
- The Tree Lopper does not hold the tree/branch whilst cutting thus minimising the risk of sudden weight increase acting to destabilise the excavator/loader.
- 360 degree rotation enables best positioning of the shear for most efficient operation.
- Wedge-shaped single blade design encourages the timber to fall in the same direction as the blade travel, during the cutting process.
- Tree Lopper can be used for handling and processing operations.
- Modular design with universal mounting enables best match of Tree Lopper and rotator with excavator/loader.
- 12 months warranty.

"Perfect Partners"



The Attachment Specialist

Exac-One Ltd
The Mount Buildings
Upton on Severn
Worcs
WR8 0QL
United Kingdom

Tel: +44(0)1684 593052
Fax: +44(0)1684 592249
info@exac-one.co.uk
www.exac-one.co.uk
Sept 2015

Tree Lopper Technical

		TL150	TL250	TL350
Excavator weight	tonnes	1.5 - 4	3.5 - 8	7 - 14
Shear weight	Kgs	140 - 190	270 - 325	520 - 575
Rotation	Deg	360	360	360
Cut dia hardwood	mm	150	250	350
Cut dia softwood	mm	200	300	400
Oil flow (minimum)	L/min	25	45	60
Oil Pressure	Bar	180 - 210	180 - 220	200 - 230
Dimension A	mm	739	1035	1400
Dimension B	mm	698	856	1250
Dimension C	mm	290	305	450

